


DATASHEET

Modbus[®] TCP/IP to Modbus[®] Serial Four-Port Gateway PLX31-MBTCP-MBS4

ProSoft Technology's Modbus[®] TCP/IP to Modbus[®] Serial four-port Serial gateway allows high-speed bi-directional data transfers between Modbus[®] TCP/IP-enabled PACs and Modbus[®] Serial devices. Modbus[®] Serial devices are widely used in nearly every industry and include SCADA systems and Power Monitors. Four Serial ports allow for connectivity of up to 400 Modbus[®] Serial devices, reducing the amount of gateways required for your application.

In addition, the gateway includes several features that allow for simplified integration, reduced commissioning time and optimized performance.



Features

- ◆ Gateway includes a SD card slot (SD card optional) for storing configuration files. This can be used for disaster recovery.
- ◆ Four Serial ports allow for connectivity of up to 400 Modbus[®] Serial devices, reducing the amount of gateways required for your application.
- ◆ Supports up to 20 simultaneous client & server connections, allowing for faster communication between devices such as HMIs, SCADA systems, power monitors and flow computers, among others.
- ◆ ProSoft Discovery Service: This utility allows your PC to see the gateway and change its default IP address without being on the same subnet as the module.
- ◆ Secure module configuration via module switch (v1.04 and greater).
- ◆ Up to 10,000 16-bit registers can be used to exchange large amounts of data.

Specifications

Modbus® TCP/IP Specifications

Specification	Description	
Supported Modbus Function Codes	1: Read Coil Status	15: Force (Write) Multiple Coils
	2: Read Input Status	16: Preset (Write) Multiple Holding Registers
	3: Read Holding Registers	22: Mask Write Holding Register (Slave Only)
	4: Read Input Registers	23: Read/Write Holding Registers (Slave Only)
	5: Force (Write) Single Coil	
	6: Preset (Write) Single Holding Register	
Supported Clients	10	
Supported Servers	MBAP: 5	
	Encapsulated: 5	
Command List	Up to 160 fully configurable Client commands	
Status Data	Error codes reported individually for each command	
Command List Polling	Each command can be individually enabled or disabled; write-only-on-data-change is available	

Modbus Serial Specifications

Specification	Description	
Command List	Up to 100 commands per Master port, each fully configurable for Function Code, slave address, register to/from addressing and word/bit count.	
Supported Modbus Function Codes	1: Read Coil Status	15: Force (Write) Multiple Coils
	2: Read Input Status	16: Preset (Write) Multiple Holding Registers
	3: Read Holding Registers	22: Mask Write Holding Register (Slave Only)
	4: Read Input Registers	23: Read/Write Holding Registers (Slave Only)
	5: Force (Write) Single Coil	
	6: Preset (Write) Single Holding Register	
Software configurable communication parameters	Baud rate: 110 baud to 115.2 kbps	
	Parity: None, Even, Odd	
	Data Size: 7 or 8 bits	
	Stop bits: 1 or 2	
	RTS on/off delay: 0 to 65535 milliseconds	
	Modbus RTU mode (binary) with CRC-16	
	Modbus ASCII mode with LRC error checking	
Floating Point Data Floating point data movement supported, including configurable support for Enron and Daniel implementations		
Polling of Command List	Configurable polling of command list, including continuous and on change of data, and dynamically user or automatic enabled.	
Status Data	Error codes available on an individual command basis. In addition, a slave status list is maintained per active Modbus Master port.	
Node Address	1 to 247 (software selectable)	
RS Interface	RS232, RS422, and RS485	
Transmit and Receive Buffer Size	255 byte Transmit character length with 0 to 65535 millisecond delay between each transmitted character	



Where Automation Connects™

Global Distribution

ProSoft Technology® products are distributed and supported worldwide through a network of over 500 distributors in over 50 countries. Our knowledgeable distributors are familiar with your application needs. For a complete list of distributors, go to our website at:

www.prosoft-technology.com

Global Support

We are there for you

All ProSoft Technology products are backed with free technical support. Contact our worldwide Technical Support team directly by phone or email.

Global Offices

We are where you are

ProSoft Technology has regional offices worldwide available to help you with all your industrial application needs. If you need help choosing a ProSoft Technology solution for your particular application, check out our contact information under distributor sales on the website at:

www.prosoft-technology.com

Whether your application is large or small, our technical professionals are there to help you choose the right communication solution.

Hardware Specifications

Specification	Description
Power Supply	24 VDC nominal 10 to 36 VDC allowed Positive, Negative, GND Terminals
Current Load	24 VDC nominal @ 300 mA 10 to 36 VDC @ 610 mA maximum
Operating Temperature	-25°C to 70°C (-13°F to 158°F)
Storage Temperature	-40°C to 80°C (-40°F to 176°F)
Shock	IEC 60068-2-27; 15G @ 11ms, 3-Axis (Operational) IEC 60068-2-27; 30G @ 18ms, 3-Axis (Non-Operational)
Vibration	IEC 60068-2-6; 5G @ 10 to 150 Hz
Relative Humidity	5% to 95% RH with no condensation
Dimensions (H x W x D)	5.38 x 1.99 x 4.38 in 13.67 x 5.05 x 11.13 cm
LED Indicators	Configuration (CFG), Error (ERR), Power (PWR), Hardware Fault (FLT), Network Status (NS), EtherNet/IP™ Class I or Class III Connection Status (EtherNet/IP Only) Module Status (MS), Module Configuration Status (EtherNet/IP Only) Ethernet Communication Port Link/Activity, and 100 mbit Serial Communication Port Receive (RX) and Transmit (TX)
Ethernet Port	10/100Mbit full- and half-duplex RJ45 Connector Electrical Isolation 1500 Vrms at 50 to 60 Hz for 60 seconds, applied as specified in section 5.3.2 of IEC 60950: 1991 Ethernet Broadcast Storm Resiliency is less than or equal to 5000 [ARP] frames-per-second and less than or equal to 5 minutes duration
Number of Serial Ports	4
Serial Port Isolation	2500 Vrms port signal isolation per UL 1577. Serial port communication signal uses RF (Radio Frequency) modulation signal as isolation media.
Shipped With Each Unit	2.5 mm screwdriver J180 Power Connector (4) RJ45-DB9M Serial Adapter Cable (serial protocol) (4) DB9 to Screw Terminal Adapter (serial protocol)
Enclosure Rating	IP20, NEMA/UL Open Type, DIN Rail

Agency Approvals and Certifications

Please visit our website: www.prosoft-technology.com



Additional Products

ProSoft Technology® offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms. For a complete list of products, visit our website at: www.prosoft-technology.com

Ordering Information

To order this product, please use the following:

Modbus® TCP/IP to Modbus® Serial Communication Gateway

PLX31-MBTCP-MBS4

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to: www.prosoft-technology.com and select *Where to Buy* from the menu.

Copyright © 2022 ProSoft Technology, Inc.

All Rights Reserved. 7/21/2022

For Public Use.

Specifications subject to change without notice.