



# IEC 60870-5-103 Master Communication Module

## MVI56-103M

The MVI56 IEC 60870-5-103 Master Communication Module allows ControlLogix backplane I/O compatible processors to interface easily with IEC 60870-5-103 compatible devices. Devices commonly supporting the protocol include relays, breakers, sub-station Communication Modules and other serial communication devices used in power monitoring.

## Features and Benefits

The MVI56-103M supports up to 32 total field devices between the module's two IEC 60870-5-103 Master ports. The module's communication ports can each be independently configured, allowing two separate field networks to be implemented. The field device data is exchanged between the MVI module and the ControlLogix processor over the backplane.

## General Specifications

- Single Slot - 1756 backplane compatible
- The module is recognized as an Input/Output module and has access to processor memory for data transfer between processor and module
- Ladder Logic is used for data transfer between module and processor. Sample ladder file included.
- Configuration data obtained from configuration text file downloaded to module. Sample configuration file included
- Local or remote rack

## Hardware Specifications

Specification	Description
Backplane Current Load	800 mA @ 5 V DC 3mA @ 24V DC
Operating Temperature	0 to 60°C (32 to 140°F)
Storage Temperature	-40 to 85°C (-40 to 185°F)
Shock	30g Operational 50g non-operational
	Vibration: 5 g from 10 to 150 Hz
Relative Humidity	5% to 95% (non-condensing)

## IEC 60870-5-103 Master Communication Module MVI56-103M

*The MVI56-103M module is the ideal solution for many applications where IEC protocol connectivity must be added to a ControlLogix system. The IEC solution is designed to address the expanding interest in the IEC protocol and the use of IEC compatible devices in industrial applications such as those in the water/wastewater, power, and oil & gas industries.*

*Compatible devices include relays, breakers, sub-station Communication Modules and other serial communication devices.*

## How to Contact Us: Sales and Support

All ProSoft Technology® products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

### Asia Pacific

+60.3.7941.2888, asiapc@prosoft-technology.com  
Languages spoken include: Chinese, Japanese, English

### Europe - Middle East - Africa

+33.(0)5.34.36.87.20, support.EMEA@prosoft-technology.com  
Languages spoken include: French, English

### North America

+1.661.716.5100, info@prosoft-technology.com  
Languages spoken include: English, Spanish

### Latin America

+52.222.264.1814, support.la@prosoft-technology.com  
Languages spoken include: Spanish, English

### Brasil

+55.11.5084.5178, brasil@prosoft-technology.com  
Languages spoken include: Portuguese, English

Specification	Description
LED Indicators	Module Status Backplane Transfer Status Application Status Serial Activity
<b>Debug/Configuration port (CFG)</b>	
CFG Port (CFG)	RJ45 (DB-9M with supplied cable) RS-232 only
<b>Application ports (PRT1 &amp; PRT2)</b>	
Full hardware handshaking control, providing radio, modem and multi-drop support	
Software configurable communication parameters	Baud rate: 110 to 115,200 baud, depending on protocol RS-232 and 422 Parity: none, odd or even Data bits: 5, 6, 7, or 8 Stop bits: 1 or 2 RTS on/off delay: 0 to 65535 milliseconds
App Ports (P1,P2) (Serial modules)	RJ45 (DB-9M with supplied cable) RS-232 handshaking configurable 500V Optical isolation from backplane
Shipped with Unit	RJ45 to DB-9M cables for each port 6-foot RS-232 configuration cable

## Functional Specifications

The MVI56-103M module supports the IEC 60870-5-103 protocol to the following specifications:

- The IEC 60870-5-103 communication driver is built in accordance to the approved IEC specification
- The module has two independent master ports, each configurable via a simple configuration file
- Supports up to 32 sessions (controlled devices) between the two ports
- Supports up to five sectors (separate databases) for each session, with individual database definition for each sector
- Total of 1000 user configurable commands to control data transfer to/from devices (controlled devices)
- Supports clock synchronization from/to the processor
- Event data received from the Control Devices updates the module database (Date and Time stamping is not stored or used by module)
- Class 1 and Class 2 delay parameters are configurable for each session
- An IEC Interoperability Document for the module is available from the web site, which fully documents data types supported by the module

## Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Compatible products in the inRAX product line also include:

### DNP 3.0 Master/Slave Communication Module for ControlLogix (MVI56-DNP)

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

## Ordering Information

To order this product, please use the following:

**MVI56-103M** IEC 60870-5-103 Master Communication Module

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

Copyright © ProSoft Technology, Inc. 2019. All Rights Reserved.  
May 3, 2019