

DATASHEET

Modbus RTU or Modbus TCP/IP to LonWorks QuickServer Gateways PS-QS-1x11-0154

The QuickServer line of communication gateways are designed to link building automation networks utilizing LonWorks with industrial control networks communicating on Modbus RTU or Modbus TCP/IP. The QuickServer gateways are available with limits of up to 250 or 500 points of application data.



Specifications

Field Connections

- Ethernet 10/100 RJ45
- Serial RS-485 terminal (up to 115K baud)
- FTT-10 LonWorks port

Environment

- Operating temperature: -40°F to 167°F (-40°C to 75°C)
- Relative humidity: 5% to 90% RH, with no condensation

Power Requirements

- 9 to 30 Vdc or Vac or 5 Vdc
- Current draw 250mA @ 12V

Other

- Configuration/Diagnostic utilities
- Capacity: 250 or 500 Points
- Table, Wall or DIN rail mount

Physical Dimensions (W x D x H)

- 4.5 x 3.2 x 1.6 in. (11.5 x 8.3 x 4.1 cm)
- 0.4 lbs (0.2 Kg)

Approvals

- TUV approved to UL 916 standard
- CE Mark
- BTL Mark (PS-QS-1010)
- RoHS Compliant
- FCC Part 15 Compliant

Ordering Information

To order this product, please use the following:

PS-QS-1011-0154	250 Points
PS-QS-1511-0154	500 Points

How to Contact Us: Sales and Support

Sales and Technical Support for this product are provided by ProSoft Technology. Contact our worldwide Sales or Technical Support teams directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com

Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, Europe@prosoft-technology.com

North America

+1.661.716.5100, support@prosoft-technology.com

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com

LonWorks® is a trademark of Echelon Corporation
Metasys® is a trademark of Johnson Controls
BACnet® is a trademark of ASHRAE