

## DATASHEET

### EtherNet/IP or DF1 to LonWorks QuickServer Gateways PS-QS-1x11-0783

The QuickServer line of communication gateways are designed to link building automation driven networks with industrial control networks. The QuickServer gateways are available with limits of up to 250 or 500 points of application data.



### Specifications

#### Field Connections

- Ethernet 10/100 RJ45
- Serial RS-485 terminal (up to 115K baud)
- FTT-10 LonWorks port

#### Environment

- Operating temperature: -40°F to 167°F (-40°C to 75°C)
- Relative humidity: 5% to 90% RH, with no condensation

#### Power Requirements

- 9 to 30 VDC or 12 to 24 VAC
- Current draw 250mA @ 12Vdc

#### Other

- Configuration/Diagnostic utilities
- Capacity: 250 or 500 Points
- Table, Wall or DIN rail mount

#### Physical Dimensions (W x D x H)

- 4.5 x 3.2 x 1.6 in. (11.5 x 8.3 x 4.1 cm)
- 0.4 lbs (0.2 Kg)

#### Approvals

Please visit our website: [www.prosoft-technology.com](http://www.prosoft-technology.com)

### Ordering Information

To order this product, please use the following:

<b>PS-QS-1011-0783</b>	250 Points
<b>PS-QS-1511-0783</b>	500 Points

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, please visit:

[www.prosoft-technology.com](http://www.prosoft-technology.com) and select *Where to Buy*.

LonWorks<sup>®</sup> is a trademark of Echelon Corporation  
Metasys<sup>®</sup> is a trademark of Johnson Controls  
BACnet<sup>®</sup> is a trademark of ASHRAE